



2780 Waterfront Pkwy. E. Dr. Suite 200 Indianapolis, IN 46214  
 Phone: 317-328-5660 Fax: 317-328-5668 Sales: 1-800-437-3188 www.calumetspecialty.com

## Product Data Sheet

If you have questions regarding this product, please contact your Sales Representative.  
 Customer Service and Technical Service can be reached at 1-800-437-3188

Product: **DUOPRIME® OIL 70**  
 Revised  
 HazMat Name: **Non-Regulated**

Product Code: **L6000-00-H**

<u>Test</u>	<u>UOM</u>	<u>Method</u>	<u>MIN</u>	<u>MAX</u>	<u>Typical</u>
VISCOSITY @ 40°C	cSt	D445	11.20	14.50	12.35
VISCOSITY @ 100°F	cSt	D445	12.00	15.70	13.35
VISCOSITY @ 100°F	SUS	D2161	66.0	80.0	71.0
API GRAVITY @ 60°F		D4052	30.0	37.0	34.4
SPECIFIC GRAVITY @ 25/25°C		D4052			.8467
COLOR, SAYBOLT		D156	30		30
CARBONIZABLE SUBSTANCES	P/F	D565	PASS		PASS
SOLID PARAFFINS		USP	PASS		PASS
WATER CONTENT	ppm	D1533		35	16
APPEARANCE		VISUAL	B&C		B&C
ACIDITY	P/F	USP	PASS		PASS
UV ABSORB(FDA21 CFR172.878)		D2269	PASS		PASS
LIMIT OF PAH	P/F	USP	PASS		PASS
LIMIT OF SULFUR COMPOUNDS	P/F	USP	PASS		PASS
INFRARED ABSORPTION	P/F	USP	PASS		PASS
THIS MATERIAL IS AN NF MIN OIL					

Copyright 2012 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Results only represent the values one would expect if the product was tested in our laboratories with our test methods on the specified date. The typical values of product properties are not frequently measured and are not based on a statistically relevant number of tests. Calumet does not represent that the typical values contained on this data sheet represent the values in the product supplied to the user. The information in this document relates only to the named product. The user is solely responsible for determining the suitability of the product for its use intended by user, including use in any process and the combination of the product with any other material.