



## Wheel Mounting Compound WM-10™

***Extreme-pressure compound for press fitting and mounting steel railroad wheels to their axles – WM-10™ polishes, seals and protects the metal surfaces for enormously improved wheel-to-axle fitting***

### Key Features & Benefits

- Improves wheel-to-axle fitting
- Reduces alignment problems
- Reduces chatter and noise
- Polishes, seals and protects metal surfaces from friction, heat and wear
- Safer than linseed oil and lead compounds
- Will not spontaneously combust
- Easy to apply
- Visible after application
- AAR approved
- Contains **Muscle Metal Treatment MT-10®** technology for improved lubrication

### Typical Applications

- Mounting steel rail car wheels to their axles

### Directions for Use

Shake or mix prior to use. Apply **WM-10™** by brush or roller to the outside ends of each axle and the inner surfaces of each wheel prior to mounting.

For industrial use only. Please see SDS for product handling, storage and disposal considerations.

### Technical Data

Appearance.....	Dark blue liquid
Odor.....	Mild petroleum
Pour point.....	- 17°F (- 27°C) D97
Initial boiling point.....	> 450°F (232°C) D1120
Flash point .....	317°F (158°C) D93
Specific gravity @ 60°F, g/cm <sup>3</sup> .....	0.9516 D1298
Density @ 15°C, g/cm <sup>3</sup> .....	0.9509 D1298
API gravity @ 60°F .....	17.2 D1298
Lbs per gal (U.S.).....	~ 7.935
Solubility.....	Insoluble (water)
Viscosity @ 40°C .....	26.12 cSt D445
Viscosity @ 100°C .....	4.52 cSt D445
Rust test, 4 hr.....	Pass (no rust) D665A

*The above properties are typical values and do not constitute a product specification.*

### Container Availability

Item WM-10-128 .....	1 U.S. gallon (3.7 L)
Item WM-10-5G.....	5 U.S. gallon (18.9 L)
Item WM-10-55G.....	55 U.S. gallon drum (208 L)

Transportable tank and other bulk containers may be available upon request.

